A	Applicant Init	iated Interviev	w Request Fo	rm		
Application No.: 09/806,304		First Na	First Named Applicant: Alain Brochez			
Examiner: Ernesto Garc		nit:3679			inal Rejection	
Tentative Participants: (1) Patrick Buechner		(2)				
(3) Ernesto Garcia						
Proposed Date of Interview: July 14, 2009			Proposed Time: 11:00AM AM/PM			
Type of Interview Reque	ested:		•			
(1) Telephonic	(2) Verso	onal (3)	3) Video Conference			
Exhibit To Be Shown or If yes, provide brief desc	YES	NO NO	0			
Issues To Be Discussed						
Issues (Rej., Obj., etc)	Claims/ Fig. #s	Prior Art	Discussed	Agreed	Not Agreed	
(1) Drawing Obj.						
(2) Spec. Obj.			\boxtimes	$\overrightarrow{\boxtimes}$		
(3) Claim Obj.			\boxtimes	\boxtimes		
(4) Claim Rejections	All	All cited		\boxtimes		
Continuation Sheet Attached						
Brief Description of Arg Discussion of formal matt			of unavailability of W0	D 2005/03345	9 as prior art;	
Discussion of deficiencies	s of proposed combina	ation of US 3,797,194, E	EP 549,554, and WO 9	31/15314; Pos	sible	
Amendment of claim 85 to	o include the features	of claim 94.				
An interview was conducted NOTE: This form should (see MPEP § 713.01). This application will not interview. Therefore, application will not interview.	d be completed by a be delayed from issu	pplicant and submitted ne because of applican	I to the examiner in a t's failure to submit a	ndvance of the	rd of this	
soon as possible.	pricant is advised to	me a statement of the		·	K 11133(b)) as	
/Patrick M. Buechner/			/Ernesto Garcia/			
Applicant/Applicant's Patrick M. Buechner	s Representative Signa	ature	Examiner/SPE	Signature		
Typed/Printed Name of 57,504		entative		·		
Registration Num	ber, if applicable					

This collection of information is required by 37 CFR 1.133. The information is required to obtain or retain a benefit by the public which is to file (and by the USPTO to process) an application. Confidentiality is governed by 35 U.S.C. 122 and 37 CFR 1.11 and 1.14. This collection is estimated to take 21 minutes to complete, including gathering, preparing, and submitting the completed application form to the USPTO. Time will vary depending upon the individual case. Any comments on the amount of time you require to complete this form and/or suggestions for reducing this burden, should be sent to the Chief Information Officer, U.S. Patent and Trademark Office, U.S. Department of Commerce, P.O. Box 1450, Alexandria, VA 22313-1450. DO NOT SEND FEES OR COMPLETED FORMS TO THIS ADDRESS. SEND TO: Commissioner for Patents, P.O. Box 1450, Alexandria, VA 22313-1450.

If you need assistance in completing the form, call 1-800-PTO-9199 and select option 2.

Privacy Act Statement

The **Privacy Act of 1974 (P.L. 93-579)** requires that you be given certain information in connection with your submission of the attached form related to a patent application or patent. Accordingly, pursuant to the requirements of the Act, please be advised that: (1) the general authority for the collection of this information is 35 U.S.C. 2(b)(2); (2) furnishing of the information solicited is voluntary; and (3) the principal purpose for which the information is used by the U.S. Patent and Trademark Office is to process and/or examine your submission related to a patent application or patent. If you do not furnish the requested information, the U.S. Patent and Trademark Office may not be able to process and/or examine your submission, which may result in termination of proceedings or abandonment of the application or expiration of the patent.

The information provided by you in this form will be subject to the following routine uses:

- The information on this form will be treated confidentially to the extent allowed under the Freedom of Information Act (5 U.S.C. 552) and the Privacy Act (5 U.S.C 552a). Records from this system of records may be disclosed to the Department of Justice to determine whether disclosure of these records is required by the Freedom of Information Act.
- 2. A record from this system of records may be disclosed, as a routine use, in the course of presenting evidence to a court, magistrate, or administrative tribunal, including disclosures to opposing counsel in the course of settlement negotiations.
- 3. A record in this system of records may be disclosed, as a routine use, to a Member of Congress submitting a request involving an individual, to whom the record pertains, when the individual has requested assistance from the Member with respect to the subject matter of the record.
- 4. A record in this system of records may be disclosed, as a routine use, to a contractor of the Agency having need for the information in order to perform a contract. Recipients of information shall be required to comply with the requirements of the Privacy Act of 1974, as amended, pursuant to 5 U.S.C. 552a(m).
- 5. A record related to an International Application filed under the Patent Cooperation Treaty in this system of records may be disclosed, as a routine use, to the International Bureau of the World Intellectual Property Organization, pursuant to the Patent Cooperation Treaty.
- 6. A record in this system of records may be disclosed, as a routine use, to another federal agency for purposes of National Security review (35 U.S.C. 181) and for review pursuant to the Atomic Energy Act (42 U.S.C. 218(c)).
- 7. A record from this system of records may be disclosed, as a routine use, to the Administrator, General Services, or his/her designee, during an inspection of records conducted by GSA as part of that agency's responsibility to recommend improvements in records management practices and programs, under authority of 44 U.S.C. 2904 and 2906. Such disclosure shall be made in accordance with the GSA regulations governing inspection of records for this purpose, and any other relevant (i.e., GSA or Commerce) directive. Such disclosure shall not be used to make determinations about individuals.
- 8. A record from this system of records may be disclosed, as a routine use, to the public after either publication of the application pursuant to 35 U.S.C. 122(b) or issuance of a patent pursuant to 35 U.S.C. 151. Further, a record may be disclosed, subject to the limitations of 37 CFR 1.14, as a routine use, to the public if the record was filed in an application which became abandoned or in which the proceedings were terminated and which application is referenced by either a published application, an application open to public inspection or an issued patent.
- 9. A record from this system of records may be disclosed, as a routine use, to a Federal, State, or local law enforcement agency, if the USPTO becomes aware of a violation or potential violation of law or regulation.

LIST OF PROPOSED CLAIMS

Claims 1 – 84 (Canceled).

7/14/09

Claim 85 (Currently Amended). A corner joint comprising two frame side members having attachment channels and mitered end portions, and at least one corner piece having two insert parts joined at connecting ends and positioned relative to one another at a predetermined angle, each insert part configured to be received by the mitered end portions of a respective one of the attachment channels of the side members,

the attachment channels being confined by an inner wall and an outer wall,

wherein a mutual interlocking between the corner piece and the side members is carried out by locking means for mutual interlocking of the corner piece and the side members, which are formed of lips defined by a pressed-in material part of the outer wall, which said lips cooperate with notches defined on the corner piece;

wherein each insert part includes at least one said notch comprising a triangular shape defined by a first side against which the lip projection is positioned which is longer than a second side over which a free end of the lip projection is pressed in;

wherein the locking means generate a pre-stress in the form of pressure on both side members and tension in the corner piece, the locking means comprising material parts which are upset-by compressing the material of the outer wall,

wherein the upset of the material parts has a useful working force on a total mitre, and

wherein a compression force has been created in the side members ends by pushing off both side members on the locking means.

the corner piece being equipped with inclined parts defining a pressure zone between the locking means and a place on the inner wall which is situated deeper in the attachment channels than the locking means, so that there can be to provide a pressure increase between said place and the locking means:

the insert parts being equipped with resilient members which are connected to one another at an angle; and

the inclined parts being respectively connected to [[the]] free ends of the resilient members;

wherein a free space or clearance free of massive material is provided on the outside corner of the corner piece, the free space or clearance extending from the locking means to at least the connecting end of the insert parts;

wherein the inclined parts form means to create a tensile force in the resilient members, since [[the]] a pressure in the inclined parts/results in a tension in the resilient members;

the tensile forces in the resilient members resulting in pressure forces in the couter and inner walls via contact between the resilient members and the outer and inner walls, thus contributing to [[the]] rigidity and the pre-stress of the obtained mitre as a whole.

Claim 86 (Previously Presented). The corner joint according to claim 85, wherein the second side extends substantially perpendicular to the longitudinal direction of the lip projection.

Claim 87 (Previously Presented). The corner joint according to claim 86, wherein said second side of the at least one notch over which the free end of the lip projection is pressed in has a buckled shape.

Claim 88 (Currently Amended). The corner joint according to claim 85 wherein use is made of stop-parts which are situated behind the pressed-in lips of the locking means, the stop parts being carried out in relief in the shape of a serration.

Claim 89 (Previously Presented). The corner joint according to claim 85, wherein each of said insert parts includes an end portion geometrically configured in

The

the shape of a triangle having an apex directed along a longitudinal axis of the respective attachment channel, each insert part defining a second leg arranged to be urged against the inner wall of the respective attachment channel, a first leg connecting at a first end with a first end of the second leg to form the apex and extending at an oblique angle relative to the second leg in a direction generally proximal to the corner portion, and a third leg extending obliquely relative to the second leg in a direction generally proximal to the corner portion and connecting to the second leg.

Claim 90 (Currently Amended). The corner joint according to claim 89, wherein the each inclined part is parts are a fragment of the an afore-mentioned first leg of the insert part.

Claim 91 (Canceled). The corner joint according to claim 90, wherein the corner joint spart of a frame in which a panel frame in which a panel frame in the by wedges, wherein the middle of the wedges is situated in the prolongation of the inclined parts.)

Claim 92 (Currently Amended). The corner joint according to claim 89, wherein each of the insert parts includes [[a]] an afore-mentioned resilient member comprising said second leg and a connecting leg situated in an extension of said second leg for connecting the end portions with the connecting ends of the insert parts; the end portion and the resilient member of each of said insert parts connected to one another at an angle so that the resilient members provide for a reactive tensile of force to the compression force which occurs in the side members ends and which have been created by pushing off both side members on the notch of the corner piece.

Claim 93 (Currently Amended). The corner joint according to claim 92, wherein the resilient members are arranged to be positioned generally along the inner wall of the respective attachment channel.

Claim 94 (Currently Amended). The corner joint according to claim 92, wherein the resilient members are arranged to be positioned generally along the inner in a contact wall of the respective attachment channel, such that the tensile force is optimally transmitted to the inside corner.

Claim 95 (Currently Amended). The corner joint according to any one of the preceding claims, wherein the corner piece is provided with positioning elements arranged to guide the insert parts into the attachment channels when positioned therein; and,

wherein the positioning elements include at least one of the following elements;

elastic press-on elements provided on the corner piece to push the inner sides of the insert parts against an inner wall of the respective attachment channel;

elastically bendable flaps provided on the insert parts at a predetermined distance from the connecting ends thereof and arranged to cooperate with the outer wall of the respective attachment channel;

support and guiding elements provided on the corner piece in the shape of a little leg having elastically bendable flaps on the corner piece arranged to cooperate with the outer wall of the respective attachment channel.

Claim 96 (Previously Presented). The joint according to claim 95, wherein the corner piece includes a clearance generally defined at an inside corner where the insert parts connect and having a hook shaped profile.

PONT

Claim 97 (New). A panel utilizing a corner joint according to any of claims.

85-90, wherein a panel is provided, the panel being wedged up by wedges, wherein the middle of the wedges is situated in the prolongation of the inclined parts.